



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web:www.coilwindingmachinechina.com



WhatsApp



WeChat

GW-IT16B/GW-IT17C LCR Meter



GW-IT16B



GW-IT17C

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web:www.coilwindingmachinechina.com



WhatsApp



WeChat

Specification: Main technical parameters:

model number		GW-IT16B	GW-IT17C
Test Frequency		50Hz-200kHz 37 frequency points	50Hz,60Hz,100Hz,120Hz,1kHz, 10kHz,20kHz,40kHz, 50kHz,100kHz,total 10 points
test parameter		C,L,X、 B、 R,G、 D,Q,ESR、 Rp.θ, Z 、 Y 、 P	C,L,X,B,R,G,D,Q,ESR,DCR,TURN.Rp、 θ、 Z 、 Y 、 P
test level		10mV-2Vrms	
Fundamental Accuracy		0.05% accuracy table prevails	
test speed		Fast: 50 times/sec, medium 20 times/sec, slow 6 times/sec (frequencies above 1kHz)	
Display range	Z ,R,X	0.01MΩ~99.9999MΩ	
	YI,G,B	0.00001μS~99.9999S	
	C	0.00001pF~9.99999F	
	D	0.00001~9.99999	
	DCR	0.01MΩ~99.9999MΩ	
	L	0.00001μH~99999.9H	
	Q	0.01~99999.9	
	θ(RAD)	3.14159~3.14159	
	θ(DEG)	-179.999°~179.999°	
	△%	-99.999%~99.999%	
	Turns-Ratio	1:0.01-100:1	
Signal Source Output Impedance		30Ω、 100Ω	
Internal DC bias voltage		0V,2V	0V,1.5V、 2V
Ranging method		Automatic, Hold	
Trigger mode		Internal, Manual, Auto, External, Bus	
Calibration Function		Open/Short, Full Frequency Zero, Spot Frequency Zero	
Equivalent circuit		Series, Parallel	
Comparator		10-position selector,, BINO~BIN9、 NG、 AUX	
		PASS、 HI、 LOW(PASS/FAIL LED display)	
Interfaces		RS232C,UsbHost,USB Device,Handler,GPIB(Option)	
Temperature and Humidity		0℃~40℃,Relative Humidity≤75%.	
Power Requirements		Voltage: 100~120 Vac or 198~242 Vac	
		Frequency: 46~64 Hz, power greater than 50 VA	
Volume(WxHxD)		310mmx115mmx315mm	
Weight(Net)		4.5Kg	

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web:www.coilwindingmachinechina.com



WhatsApp



WeChat

FEATURES:

- 1.Highly comparable with international brand LCR bridge test data
(Keysight,WK)
- 2.Keyboard lock function, power-down data protection function
- 3.List scanning function, open circuit, short circuit, load correction function
- 4.Simplified Chinese and English operating languages
- 5.Test data, test conditions saving (USB flash disk or internal)
- 6.Test voltage, current automatic balance adjustment function (ALC)
- 7.50 sets of test files inside the instrument and 500 sets of test files on USB
flash disk can be recalled at any time
- 8.U disk can support the format FAT16, FAT32 file system

Brief statement

GW-IT16B/GW-IT17C digital LCR bridge is a new generation of impedance tester with color TFT display screen, its basic accuracy of 0.05%, 50Hz~200kHz frequency range can be used to meet the incoming inspection, shipment inspection, to provide product quality assurance.

Ordering Information

- GW-IT16B:50Hz-200KHz LCR Digital Bridge
- GW-IT17C:50Hz-100KHz LCR digital bridge with lap count function.

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web: www.coilwindingmachinechina.com



PRACTICAL APPLICATION:

TRAINNING CUSTOMER TO OPERATE WINDING MACHNE :

1.All service engineers with 10 years experience are gotten special technology training, who can deal with various breakdown problem.

2.Guide the user to use accurately and how to maintain the product.

Provide free consultation about production process technology of electronic products.

3.In order to guarantee the machine used normally, we'd have training on how to operate, use and maintain our product by English manual, video, guiding on line.

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web: www.coilwindingmachinechina.com



WhatsApp



WeChat

PACKAGING:

Packaging Material: Carton/Wooden case with foam inside.

1. General package(Paper carton or plastic bag): For small equipped parts for Toroidal Transformer Winding Machine, Package it with form and pack paper to guarantee unbroken during the transport.

2. Wooden case package: For larger scale Toroidal Winding machine, we have special skilled carpenter, who would make the proper wooden case with exact thickness, density, length. The up arrow ↑ marked on the outer wooden case. Buffer material would be put in the wooden case to prevent crack and shock.



Below is the name of all listed accessories for the machine and construction diagram.

(Note: Different machines have different equipped parts)

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area, Dongli Distr, Tianjin, China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web: www.coilwindingmachinechina.com



WhatsApp



WeChat

FACTORY:

We-GREWIN INDUSTRIAL GROUP is expert in winding machines lines for 28Years. Our Grewin have ISO9001:2015,CE approvals,Machines'Patents,"high-tech enterprises"by the government.



GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.